




STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION



SECTIONS THRU SLAB OR DECK BEAM

\*\*\* Dimension shown is minimum required embedment into concrete.  
If hot-mix asphalt wearing surface is present, minimum embedment shall be in addition to wearing surface depth.

\*\*\*\* If existing deck beam is to remain in place after stage construction, embedment shall only be into wearing surface and not into existing deck beam concrete.




STEEL RETAINER PLATE 1" x 7" x 10"

\* Required only with Detail II

\*\* Wood blocks may be omitted when required to provide minimum stage traffic lane width. When the wood blocks are omitted, the concrete barrier shall be in direct contact with the steel retainer plate.

"W" = Top bars spacing + 4"

TEMPORARY CONCRETE BARRIER  
FOR STAGE CONSTRUCTION  
STRUCTURE NO. 016-0315

<div></div> <div>LIN ENGINEERING, LTD. Consulting Engineers Chatham, Illinois</div>	SHEET NO. 3  17 SHEETS	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
		348	(0708.1&2323.5)B	COOK	47	14	
					CONTRACT NO. 60D69		
		Designed By: ADB Date: March, 2003		Checked By: WTH File: 016-0315.dgn	ILLINOIS FED. AID PROJECT		